Datasheet and description



Avide Exit Light Surface mounted IP65

Product code: AEXITL-IP65

Brand link: avidelighting.com/qr/AEXITL-IP65

ID: AB-190518

Company name: Bramcke Hungary Kft.

Company address: Kishatár utca 17., 4031 Debrecen



Date of issue: 2025-01-15

Page: 1/3

SPECIFICATIONS

EAN code: 5999097926742

Warranty:

Color: White

Material:

Working temperature: -10 - +45 °C Packaging: $1/b \ 12/c \ 864/p$

Certifications:

Accessories: Self-adhesive stickers

TECHNICAL DETAILS

Wattage: 2.8W

Voltage: 220-240V

Beam angle:

Dimmability: No
Lumen output: 80lm
Color temperature: 6 000K
Lifetime: 50 000h

Energy class:

Type of LED: DIP

Number of LEDs:

Battery type: Ni-Cd 3-6V, 500mAh

Emergency light: 180min
Recharge time: 24h
IP standard: IP65

BOX PICTURE



Datasheet and description



Avide Exit Light Surface mounted IP65

Product code: AEXITL-IP65

Brand link: avidelighting.com/qr/AEXITL-IP65

ID: AB-190518

Company name: Bramcke Hungary Kft.

Company address: Kishatár utca 17., 4031 Debrecen



Date of issue: 2025-01-15

Page: 2/3

PRODUCT SIZE

Width: 268.5mm
Height: 36.2mm
Depth: 120mm

CARDBOARD BOX

EAN: 5999097926742 Packaging: 1/b 12/c 864/p

Dimensions: 275mm x 130mm x 43mm

Net weight: 416g Gross weight: 485g

CARTON

EAN: 5999097926759 Packaging: 1/b 12/c 864/p

Dimensions: 400mm x 293mm x 200mm

Net weight: 4.992kg
Gross weight: 5.82kg

PALLET EXAMPLE

Height:

Width: 120cm (std Euro pallet)

Mepth: 80cm (std Euro pallet)

Cartons per pallet: 72carton/pallet


Cartons per row:

Net weight: 359.424kg Gross weight: 419.04kg

PRODUCT PICTURE



PRODUCT OUTLINE



Datasheet and description



Avide Exit Light Surface mounted IP65

Product code: AEXITL-IP65

Brand link: avidelighting.com/qr/AEXITL-IP65

ID: AB-190518

Company name: Bramcke Hungary Kft.

Company address: Kishatár utca 17., 4031 Debrecen



Date of issue: 2025-01-15

Page: 3/3

PRODUCT DESCRIPTION

The Avide LED exit light is an edge-lit product with adhesive pictograms and 1 W output providing constant light. Back-up time in the case of a power failure is 180 minutes.

It can be mounted in four different ways (the sign can be mounted on the wall and ceiling alike and can also be rotated 90 °).

- suspended from a chain (80 cm)
- mounted on the ceiling
- mounted on a vertical wall in two different ways. Note that the product may also be mounted laterally with the set provided!

<u>Contents of the box</u>: light fixture, clear acrylic sheet, lateral mounting kit, 80 cm suspension chain, two types (horizontal, 45°) of direction indicating arrows, pictograms with figure running to the right and left, complete instructions for use and installation in English and Hungarian.