

Avide LED Glass Tube 9W G13 600mm NW 4000K High Lumen 150lm/W

Product code: AB600T8-9W-NW-GL-HL
Brand link: avidelighting.com/qr/AB600T8-9W-NW-GL-HL
ID: AB-190518
Company name: Bramcke Hungary Kft.
Company address: Kishatár utca 17., 4031 Debrecen

QR code:



Date of issue: 2025-01-15

Page: 1/3

SPECIFICATIONS

EAN code: 5999097923581
Warranty: 5year(s)
Working temperature: -20 - +40°C
Packaging: 1/b 25/c 1350/p
Certifications: CE

PRODUCT PICTURE



TECHNICAL DETAILS

Wattage: 9W
Voltage: 180-265V
Beam angle: 240°
Dimmability: No
Lumen output: 1 350lm
Color temperature: 4 000K
Lifetime: 25 000h
Energy class: A+
Type of LED: SMD
IP standard: IP20

Avide LED Glass Tube 9W G13 600mm NW 4000K High Lumen 150lm/W

Product code: AB600T8-9W-NW-GL-HL
Brand link: avidelighting.com/qr/AB600T8-9W-NW-GL-HL
ID: AB-190518
Company name: Bramcke Hungary Kft.
Company address: Kishatár utca 17., 4031 Debrecen



Date of issue: 2025-01-15

Page: 2/3

PRODUCT SIZE

Diameter: 26mm
Length: 600mm

PRODUCT PICTURE



CARDBOARD BOX

EAN: 5999097923581
Packaging: 1/b 25/c 1350/p
Dimensions: 30mm x 30mm x 645mm
Net weight: 111.5g
Gross weight: 120g

PRODUCT OUTLINE

CARTON

EAN: 5999097923598
Packaging: 1/b 25/c 1350/p
Dimensions: 665mm x 215mm x 195mm
Net weight: 2.7875kg
Gross weight: 3kg

PALLET EXAMPLE

Height:
Width: 120cm (std Euro pallet)
Mepth: 80cm (std Euro pallet)
Cartons per pallet: 54carton/pallet
Cartons per row:
Net weight: 150.525kg
Gross weight: 162kg

Avide LED Glass Tube 9W G13 600mm NW 4000K High Lumen 150lm/W

Product code: AB600T8-9W-NW-GL-HL
Brand link: avidelighting.com/qr/AB600T8-9W-NW-GL-HL
ID: AB-190518
Company name: Bramcke Hungary Kft.
Company address: Kishatár utca 17., 4031 Debrecen



QR code:
Date of issue: 2025-01-15

Page: 3/3

PRODUCT DESCRIPTION

The Avide LED dust- and moisture-proof fixtures for tubes represent the energy-saving versions of traditional fittings. The fixtures of different lengths replacing the tube fixtures have a built-in LED panel that guarantees energy-saving operation. In terms of the material used, the products have a break-resistant cover. Due to the IP65 protection of the fixture, it is protected from dust and moisture, thus can also be operated at places with higher exposure to dust and humidity.

The product range includes a 1 and 2 LED design, in lengths of 0.6, 1.2 and 1.5 meter lengths, with a transparent cover.

OUR IP protected fixture category includes numerous additional products. Learn more about these on the following link.